



DA420™ Thermo-Anemometer



- ✓ High accuracy: $\pm 1.0\%$ of reading
- ✓ Rugged metal probe and vane
- ✓ Intuitive user interface design
- ✓ Ultra low speed sensitivity down to 40 ft/min
- ✓ Industrial grade enclosure and probe
- ✓ Measure airflow and temperature in extreme environments from -20° to 100°C
- ✓ Minimum and Maximum air speed and temp
- ✓ Analog voltage output and Communication options
- ✓ Low power, high performance, RISC microprocessor
- ✓ Advanced software algorithm for precise probe calibration

The Pacer DA420 Rotating Vane Anemometer is a high quality instrument providing highly accurate air velocity and temperature measurements in harsh environments via a user-friendly & intuitive interface. Applications include indoor air quality, process control, flow hood monitoring, and many other applications where precise air flow and temperature measurement is required.

Pacer Sales and Engineering
PO Box 726
60 Dunbar Street
Keene, New Hampshire 03431 USA
Email: sales@pacer-instruments.com
Phone: 603-352-0187
Fax: 603-352-1036

www.pacer-instruments.com

Pacer Calibration and Service
1450 First Avenue
Chippewa Falls, WI 54729 USA
Email: service@pacer-instruments.com
Phone: 715-723-1141
Fax: 715-723-7890



DA420™ Thermo-Anemometer

SPECIFICATIONS

Ranges

Air Probe APT275: 40 to 7800 FPM (feet per minute)
0.2 to 40.00 MPS (meters per second)

Air Probe APT100: 60 to 6800 FPM
0.3 to 35.00 MPS

Temperature (using either air velocity probe head):
-4° to 212°F (-20° to 100°C)

Accuracy

Air Velocity: $\pm 1.0\%$ of Reading ± 1 digit
Temperature: $\pm(0.3^\circ\text{C} + 0.2\%$ of reading in $^\circ\text{C}$)
temperature accuracy examples: $\pm 0.3^\circ\text{C}$ at 20°C
 $\pm 0.5^\circ\text{F}$ at 68°F

Resolution

Air Velocity: 1 FPM or 0.01 MPS
Temperature: 0.1°F or $^\circ\text{C}$

Display

0.5" LCD, 4 digits, with LED backlight

Operating Temp

Instrument: 32° to 125°F / 0° to 50°C
Air Probe: -4° to 212°F / -20° to 100°C

Power Supply

3 AA alkaline batteries

Battery Life

Approximately 150 hours

Dimensions

Instrument: 6.5 inch X 3.25 inch X 1.5 inch
Probe APT275: 2.75 inch diameter
Probe APT100: 1 inch diameter

Instrument Options Available

- Protective Rubber Boot and Splash-Proof Seal
- USB communications
- RS232 communications
- Analog 0-5 Volt output
- Additional Probe PN APT100 or APT275
- Extra extension and/or flexible rods
- Custom cable lengths

DA420 comes complete with

- 1 pc. rotating vane probe head with temperature sensor: APT275 or APT100
- 3 pc. extension rod w/ handle grip
- 1 pc. flexible rod
- 1 pc. 5' connecting cable
note: cable attached to APT100 probe
- 3 pc. AA 1.5 V alkaline batteries
- 1 pc. carrying case



Sales and Engineering

Pacer Instruments, Inc
PO Box 726
60 Dunbar Street
Keene, New Hampshire 03431 USA
Email: sales@pacer-instruments.com
Phone: 603-352-0187

www.pacer-instruments.com

Calibration and Service

Pacer Instruments, Inc
1450 First Avenue
Chippewa Falls, WI 54729 USA
Email: service@pacer-instruments.com
Phone: 715-723-1141